

**IC-910H Multi-mode Tri band Amateur (2m/70cm & Optional 23cm)
Base Transceiver.**

Accessories

| | |
|--------|--|
| AG25 | Preamplifier (145 MHz Band) (Weather proof/Masthead) |
| AG35 | Preamplifier (440 MHz Band) (Weather proof/Masthead) |
| AG2400 | 2.4G Down Converter |
| CT17 | Level Converter CI-V, with RS232 Cable |
| CR293 | Crystal, high stability |
| FL132 | CW Narrow Filter (for main band, 500Hz/-6dB) |
| FL133 | CW Narrow Filter (for sub band, 500Hz/-6dB) |
| HM36 | Standard Handheld Microphone |
| MB5 | Mounting Bracket |
| MB23 | Carry Handle |
| PS125 | DC Power Supply |
| SM20 | Desk Microphone, up/down, low cut |
| SP21 | Speaker:base, 8 Ohm, 5W |
| SP23 | Speaker:base, 8 Ohm, 5W with filter |
| UT102 | Voice Synthesizer |
| UT106 | DSP Unit |
| UX910 | 1200 MHz Band Module |

Cables

| | |
|----------|--|
| OPC-025D | DC power cable, 30A |
| SP20 | External speaker with 4 audio filters, headphone jack (80 ohm, 5W max input power) |